



## COMMERCIAL & RESIDENTIAL

**LLD Series: High-Lumen LED Disks for Flush Installation on 3/0 or 4/0 boxes, with Lens**



**TITLE  
20 & 24  
Compliant**




### 10" & 13" LED Flush Mount Disk w/ Lens

<b>Catalog Numbers</b>	LLD-10-3K-WH	(10" White 3000K)
	LLD-13-3K-WH	(13" White 3000K)
	LLD-10-3K-BK	(10" Black 3000K)
	LLD-13-3K-BK	(13" Black 3000K)
	LLD-10-3K-NI	(10" Nickel 3000K)
	LLD-13-3K-NI	(13" Nickel 3000K)
	LLD-10-3K-BZ	(10" Bronze 3000K)
	LLD-13-3K-BZ	(13" Bronze 3000K)



Dimmable, damp rated, LED disk constructed with heavy duty steel and with a painted polyester-coat finish. Fast and easy installation on either 3/0 or 4/0 boxes. 3 Year warranty against failure or lumen-loss beyond acceptable range. Light weight. Secure, flat installation on ceiling or wall.

	13"	10"
<b>Lumens</b>	3200	2000
<b>CRI</b>	>92	>92
<b>Energy Star</b>	Yes	Yes
<b>Rated Life</b>	50,000 hours	50,000 hours
<b>L-Rating (lumens at and of rated life)</b>	L80 (warranted to exceed 36,000 hrs)	L80 (warranted to exceed 36,000 hrs)
<b>Installation Support</b>	3/0 or 4/0 boxes	3/0 or 4/0 boxes
<b>Energy Usage</b>	48W	32W
<b>Finishes Available</b>	White, Nickel, Bronze, Black	White, Nickel, Bronze, Black
<b>Beam Spread</b>	150 degree	150 degree
<b>Dimmable</b>	Yes	Yes
<b>Dimmable To</b>	10%	10%
<b>UL/Intertek</b>	Yes	Yes
<b>CA Title 20 &amp; 24</b>	Yes	Yes
<b>Kelvin</b>	3000K	3000K
<b>Damp Rated</b>	Yes	Yes
<b>Rated Voltage</b>	AC120V, 50/60Hz	AC120V, 50/60Hz
<b>Harmful Blue Light Rating*</b>	Excellent (< .6)	Excellent (< .6)
<b>Flicker*</b>	Excellent* (2.64% at 40Hz, 21.65% at 1000Hz)	Excellent* (2.64% at 40Hz, 21.65% at 1000Hz)

\* Note: Harmful blue light and Flicker ratings are not officially monitored, governed, regulated, or reviewed by a governing or testing agency, and while given numbers above are accurate as per Intertek inspections, the "Excellent" designation is the opinion of manufacturer and subjective.



## Spectroradiometric Parameters



Tested Criteria Item	Result
Input Voltage	120.0V
Input current	0.2693A
Total power	32.22W (10")   48.26W (13")
Power factor	0.9964
Current on ea. LED module	67.3mA (10")   67.2mA (13")
Measured max temp (°C)	63.6
Temp Limit (°C)	105
Color Rendering (Ra)	Samp 1: 97.0   Samp 2: 97.2   Samp 3: 97.1

## ORDERING / PART NUMBER FORMAT

LLD	10	3K	WH
PRODUCT SERIES LLD	SIZE (RIM TO RIM) 10 = 10" 13 = 13"	KELVIN (COLOR TEMP) 3K = 3000 Kelvin	FINISH WH = White BK = Black NI = Nickel BZ = Bronze